CERTIFICATE OF CONFORMITY



1. FIRE PROTECTION EQUIPMENT

2. Certificate No:

FM23FPUS0185

3. Equipment:

(Type Reference and Name)

Control Inert Inergen Clean Agent Fire

Extinguishing Systems

4. Name of Listing Company:

Fire Eater A/S

5. Address of Listing Company:

Vølundsvej 17, 3400 Hillerød, Denmark

6. The examination and test results are recorded in confidential report number:

3039375 dated 24th May 2013

7. FM Approvals LLC, certifies that the equipment described has been found to comply with the following Approval Standards and other documents:

FM 5600:2023

- 8. This certificate relates to the design, examination and testing of the products specified herein. The FM Approvals surveillance audit program has further determined that the manufacturing processes and quality control procedures in place are satisfactory to manufacture the product as examined, tested and Approved.
- 9. Approval Guide Listing Category:

Clean Agent Fire Extinguishing Systems

Certificate issued by:

9.8. Marquestint

J.E. Marquedant

VP, Manager - Electrical Systems

5 December 2024

Date

To verify the availability of the Approved product, please refer to www.approvalguide.com

THIS CERTIFICATE MAY ONLY BE REPRODUCED IN ITS ENTIRETY AND WITHOUT CHANGE

FM Approvals LLC. One Technology Way, Norwood, MA 02062 USA
T: +1 (1) 781 762 4300 F: +1 (1) 781 762 9375 E-mail: information@fmapprovals.com www.fmapprovals.com
F 320 (Jul 24)



CERTIFICATE OF CONFORMITY



US Certificate of Conformity No: FM23FPUS0185

10. Description of Equipment:

System Designation:	Control Inert Inergen Clean Agent Fire Extinguishing Systems	
System Type:	Engineered	
•		
Agent Identification:	Inergen (Identified as IG-541 in NFPA 2001)	
Available Agent Storage Pressures:	200 bar, 300 bar	
Minimum and Maximum Agent Storage Temperatures:	60°F to 80°F (15°C to 27°C) for multiple hazard, unbalanced systems	
	32°F to 150°F (0°C to 65°C) for single hazard, unbalanced systems	
Available Nozzle Types:	360°	
Maximum Nozzle Area of Coverage:	24 ft by 24 ft (7.3 m by 7.3 m), 17 ft (5.2 m) maximum distance to farthest corner	
Minimum and Maximum Nozzle Installation Height per Row:	0.3 ft to 15.4 ft (0.1 m to 4.7 m)	
Minimum and Maximum Height of Protected Area per Nozzle Row:	1.0 ft to 15.4 ft (0.3 m to 4.7 m)	
Minimum Design Concentration for Hazard Class:	Class A – 37.45% Class B – 41.55%	
Design, Installation, Operation, and Maintenance Manual:	Fire Eater Control Inert Ci Manual for UL Listed, FM Approved Extinguishing System, P/N Ci Manual , Rev. 2024-11	
Flow Calculation Software:	Fire Eater Inergen Management Tool (IMT) flow calculation program Version 2.2.0, utilizing Flow Sim Engine dated 2014-08-27	
	or	
	Fire Eater Inergen Management Tool (IMT) flow calculation program 3.x.y (where x and y can be any number), utilizing Flow Sim Engine dated 2018-08-02	
Limitations or Exceptions to the Approval:	Limitations as defined in the manual and software and listed above	

To verify the availability of the Approved product, please refer to www.approvalguide.com





CERTIFICATE OF CONFORMITY



US Certificate of Conformity No: FM23FPUS0185

Approved Filling Facilities:	Air Products Turanka 94 62700 Brno Czech Republic Shanghai Leinuo Security Technology Co., Ltd Building 1, No. 919, Xin Kang Road Qing Pu District, Shanghai China
	PG Depot Decin (Air Products spol s.r.o.) J.S. Baara 2063/21 405 02 Decin Czech Republic

11. Test and Assessment Procedure and Conditions:

This Certificate has been issued in accordance with FM Approvals US Certification Requirements.

12. Schedule Drawings

A copy of the technical documentation has been kept by FM Approvals.

13. Certificate History

Details of the supplements to this certificate are described below:

Date	Description
24 May 2013	Original Issue.
14 September 2023	Supplement 1: Report Reference: PR465951 dated 14 th September 2023. Description of the Change(s): Converted certificate format, added PG Depot Decin (Air Products spol s.r.o.) filling facility.
5 December 2024	Supplement 2: Report Reference: PR463044 dated 5 December 2024. Description of the Change(s): Addition of new components. Manual revised.

To verify the availability of the Approved product, please refer to www.approvalguide.com



